



BASIC PART NUMBER	THREAD UNJF-3A	ØA +.005 -.005	ØB +.0005 -.0005	C MIN	ØD +.000 -.015	E MIN	H	ØJ +.010 -.030	M	ØN ±.005	Q	R ±.005	T REF	U REF	W MAX/MIN	X	Y
EWB 926-3	.1900-32	.364	.1890	.277	.250	.098	.214	.156	.062	.037	.040	.036	.419	.04	.251/.243	.005	.0045
EWB 926-4	.2500-28	.470	.2490	.347	.312	.135	.254	.180	.062	.037	.042	.036	.531	.04	.313/.304	.005	.0045
EWB 926-5	.3125-24	.580	.3115	.419	.375	.162	.319	.215	.070	.055	.050	.036	.611	.05	.376/.367	.006	.0045
EWB 926-6	.3750-24	.720	.3740	.561	.500	.197	.405	.297	.070	.055	.075	.052	.707	.05	.502/.492	.008	.0045
EWB 926-7	.4375-20	.825	.4365	.631	.562	.228	.464	.320	.070	.055	.083	.052	.814	.06	.564/.553	.009	.0045
EWB 926-8	.5000-20	.945	.4990	.703	.625	.254	.530	.380	.094	.055	.098	.052	.926	.06	.627/.616	.010	.0060
EWB 926-9	.5625-18	1.050	.5610	.846	.750	.287	.600	.440	.094	.055	.118	.068	1.025	.07	.752/.741	.011	.0060
EWB 926-10	.6250-18	1.190	.6235	.917	.812	.327	.673	.469	.094	.055	.125	.068	1.152	.07	.814/.803	.012	.0060
EWB 926-12	.7500-16	1.420	.7485	1.059	.937	.380	.806	.570	.094	.055	.152	.068	1.314	.08	.940/.928	.015	.0060
EWB 926-14	.8750-14	1.640	.8735	1.271	1.125	.438	.965	.750	.125	.055	.211	.068	1.520	.09	1.127/1.115	.018	.0090
EWB 926-16	1.0000-12	1.875	.9985	1.414	1.250	.493	1.095	.843	.125	.055	.230	.068	1.769	.09	1.252/1.239	.020	.0090
EWB 926-18	1.1250-12	2.095	1.1230	1.628	1.437	.556	1.243	.953	.125	.055	.280	.068	1.960	.13	1.440/1.427	.022	.0090

- MATERIAL: ALLOY STEEL PER AMS 6487.
- HEAT TREATMENT: 260 KSI MINIMUM ULTIMATE TENSILE STRENGTH. HRC 51-54. 156 KSI MINIMUM SHEAR STRENGTH
- FINISH: DIFFUSED NICKEL-CADMIUM PLATE PER AMS 2416 WITH CHROMATE TREATMENT.
- PART NUMBER: EWB 926 - 6 H - 12 = .3750-24 BOLT, DIFFUSED NICKEL-CADMIUM PLATE PER AMS 2416 WITH CHROMATE TREATMENT, 1.457 LONG, .750 GRIP, CROSSDRILLED HEAD
 = GRIP LENGTH IN SIXTEENTHS
 "H" = CROSSDRILLED HEAD
 NO LETTER = NO CROSSDRILLED HEAD
 = NOMINAL DIAMETER IN SIXTEENTHS
 BASIC PART NUMBER
 LENGTH = NOMINAL GRIP + "T REF"
- REFERENCE DIMENSIONS ARE FOR DESIGN PURPOSES AND ARE NOT INSPECTION REQUIREMENTS.
- DIMENSIONS ARE IN INCHES.
- CHAMFER "U REF X 45° APPROX." PLUS INCOMPLETE THREADS NOT TO EXCEED TWO PITCHES.
- FOR WEIGHTS SEE SPS SD. 300.53951.

INFORMATION ON THIS DOCUMENT IS A TRADE SECRET, PROPRIETARY, AND SHALL NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN AUTHORIZATION OF SPS TECHNOLOGIES.

TOLERANCES ±.010 AND ±2' SURFACE ROUGHNESS 125/ UNLESS OTHERWISE NOTED		FSCM NO. 56878 CUSTODIAN: JENKINTOWN, PA.	STANDARDS AND SPECIFICATIONS SPS-B-640 APPENDIX 6.2
DRAWN: STEVE FOSTER DATE: 11/29/90 APPROVED: L. KLINE DATE: 11/29/90 APPROVED: TAR		TITLE BOLT, 12 POINT, TENSION 260 KSI MINIMUM TENSILE STRENGTH APPLICATIONS TO 900°F	PART NUMBER: EWB 926